

## Ongoing Maintenance Following Application Of SuperTop™ and SuperTop/HD Renewable Finishes

***SuperTop™ and SuperTop/HD are high-quality, high-durability resin/waxes. As with any floor finish, regular cleaning and periodic renewal are required. Frequency will depend on traffic patterns and, for ground level sites, outside weather conditions.***

### **SWEEPING and CLEANING**

*Floor should be dust-mopped or swept with a soft broom to remove surface dust/dirt and, in certain climates, to remove sand and salts carried in from the outside. Granular material on the surface will act as “sandpaper” under foot traffic.*

*Use of walk off mats is recommended during particularly inclement weather.*

***Shoe heels and rubber cart scuffmarks will be left on any flooring surface including vinyl tile, dimensional stone and concrete.***

*These can be removed on a spot basis using the cleaning method below, or lightly buffed out with a lightweight, slow speed, single action floor machine and white pad.*

- ◆ ***In a 2 ½ gallon bucket, mix 3 ounces StoneClean™ “104” Concentrate with 2 to 2 ¼ gallons water (or 1 part “104”: 80-100 parts water). IMPORTANT NOTE: You MUST dilute the “104” as indicated. Otherwise you will leave streaks.***
- ◆ ***Clean using a SPONGE MOP or FOAM SQUEEGEE. Change cleaning solution as needed. A lightweight, low speed single action floor machine with a white pad can also be used for large installations and is sometimes needed for high traffic. No rinsing is required since “104” does leave residues. If heavily buffed, renewal with SuperTop may be required.***

*NOTE: String mops are not effective in cleaning of smooth surfaces since they do not deliver any pressure like a sponge or squeegee to remove scuffmarks.*

### **SuperTop and SuperTop/HD RENEWAL FOR HIGH WEAR AREAS**

- ◆ ***Clean floor as above and let dry. For very contaminated floors, use floor machine (as above) rather than squeegee or mop.***
- ◆ ***Apply SuperTop or SuperTop/HD per standard directions to indicated areas.***
- ◆ ***Allow to dry.***

*For stripping, if needed, use RJSC StoneClean & Strip or contact RJSC.*

**Subject to job site cautions in MSDS.  
Subject to RJSC Limited Warranty.**